Serial Number: 10/708,184

IN THE CLAIMS

Cancel claims 1 and 6, and amend claims 2-5 and 7-9 as follows:

1. (Cancel)

2. (Currently Amended) ~~The command multiplier of claim 1 wherein there are~~

A command multiplier that generates sets of command, address, and data inputs

(CAD) from a seed set having a plurality of bits provided at a low frequency by a

BIST, to an embedded memory at a high frequency, comprising:

a directive register;

a logic unit;

a multiplexer for time-multiplexing n generated CAD sets to the memory system

at a frequency n times greater than the frequency at which the seed CAD set is

received;

c directive registers corresponding to c seed CAD bits, each register having n

directive bits corresponding to the n CAD sets to be generated; and

n logic units (LUs) corresponding to the n CAD sets to be generated, each LU

taking as an input the i th bit of the seed CAD and one of the n bits from the i th

directive register.

3. (Currently Amended) ~~The command multiplier of claim 1 wherein there are~~

A command multiplier that generates sets of command, address, and data inputs

(CAD) from a seed set having a plurality of bits provided at a low frequency by a

BIST, to an embedded memory at a high frequency, comprising:

a directive register;

a logic unit;

a multiplexer for time-multiplexing n generated CAD sets to the memory system

at a frequency n times greater than the frequency at which the seed CAD set is

received;

c directive registers corresponding to c seed CAD bits, each register having n

directive bits corresponding to the n CAD sets to be generated; and

n logic units (LUs) corresponding to the n CAD sets to be generated, each LU

taking as an input the i th bit of the seed CAD, one of the n bits from the i th

directive register, and the binary-encoded time interval, m.

4. (Currently Amended) The ~~command multiplier of claim 1 wherein there are~~

A command multiplier that generates sets of command, address, and data inputs

(CAD) from a seed set having a plurality of bits provided at a low frequency by a

BIST, to an embedded memory at a high frequency, comprising:

a directive register;

a logic unit;

a multiplexer for time-multiplexing n generated CAD sets to the memory system

at a frequency n times greater than the frequency at which the seed CAD set is

received;

c directive registers corresponding to c seed CAD bits, each register having n

directive bits corresponding to the n CAD sets to be generated; and

n logic units (LUs) corresponding to the n CAD sets to be generated, each LU

taking as an input the i th bit of the seed CAD, one of the n bits from the i th

directive register, and a binary-encoded value corresponding to its directive bit

input.

5. (Currently Amended) A command multiplier that generates multiple sets of

command, address, and data inputs (CAD) from a seed CAD set having a plurality

of bits provided at a low frequency to a memory system at a high frequency,

comprising:

c directive registers corresponding to c seed CAD bits, each register having one or

more directive bits;

a logic unit (LU) taking as an input the i th bit of the seed CAD, all of the bits

from the i th directive register, and a binary-encoded time interval, m; and

a multiplexer for time-multiplexing n generated CAD sets to the memory system

at a frequency n times greater than the frequency at which the seed CAD set is

received; .

6. (Cancel)

7. (Currently Amended) ~~The command multiplier of claim 6 which includes~~

A command multiplier that generates multiple sets of command, address, and data inputs (CAD) from a seed CAD set having a plurality of bits provided at a low frequency to a memory system at a high frequency, comprising:

a register;

an arithmetic logic unit (ALU);

a multiplexer for time-multiplexing n generated CAD sets to the memory system at a frequency n times greater than the frequency at which the seed CAD sets are received; and

address offset registers corresponding to the n CAD sets to be generated, each contents of which is added to the corresponding seed address by the ALU to generate one of the n output addresses.

8.(Currently Amended) ~~The command multiplier of claim 6 which includes~~ A command multiplier that generates multiple sets of command, address, and data inputs (CAD) from a seed CAD set having a plurality of bits provided at a low frequency to a memory system at a high frequency, comprising:

a register;

an arithmetic logic unit (ALU);

a multiplexer for time-multiplexing n generated CAD sets to the memory system at a frequency n times greater than the frequency at which the seed CAD sets are received; and

BUR920040037US1   5

op-code registers corresponding to the n CAD sets to be generated, each contents

of which is combined with the corresponding seed CAD control signals to

generate one of the n of that control signal.

9. (Currently Amended) A method for generating multiple sets of command,

address, data inputs (CAD) from a seed CAD set having a plurality of bits

provided by a BIST at low speed f_{BIST} to a memory system at a higher speed f_{MEM}

comprising the steps of:

Loading a command multiplier register from the BIST;

Sending ~~ending~~ the seed CAD set from the BIST to a logic block to generate n

CAD sets; and

providing the n CAD sets to a multiplexer to send the CAD sets to the memory

system at f_{MEM}.

10. (Original) The method of claim 9 wherein the logic block is either a logic unit
   or an ALU.

BUR920040037US1   6